



Battery Lift Table Technical Specifications

3-Tier Battery Powered Platform Hydraulic Stacker

Ideal for battery installers with extended and frequent use, this lift allows one person to easily lift and transport extra-heavy loads, helping prevent lift injuries. Meets ASME B56.10 specifications. 1,000 lb lift capacity. Remote control, floor lock and safety screen are standard on all models. With a minimally charged battery, unit can be used while recharging. Three light LED charge status indicator. Easy to read illuminated battery status voltmeter. Remote control with magnetic base and 12 ft. coiled wire gives user the option to control unit from any position around it.

Acran Item Number	5BLW802424
Load Capacity (lbs.)	1000
Max. Lifting Height (in.)	80
Min. Lifting Height (in.)	5.75
Platform Length (in.)	24
Platform Width (in.)	24
Wheels	4
Weight (lbs.)	457
Overall Height (in.)	92
Depth (in.)	36
Width (in.)	25.5
Leg ID/OD (in.)	15/21
Load Center (in.)	15



Manufacturing Facility:
105 Snyder Road
South Plainfield, NJ 07080

ACRAN SPILL CONTAINMENT

T 877- 227- 2615 F 908-769-6991 Email sales@acran.com

Corporate Headquarters:
599 Albany Ave.
No. Amityville, NY. 11701